

ANTIGRAFFITIK

ANTIGRAFFITI COATING

Description ANTIGRAFFITIK is a permanent anti-vandal coating for the protection of concrete, masonry, wood, metal and pre-existing coatings. It offers excellent performance against outdoor elements such as rain, sun and extreme temperature variations. It is a one-component product that cures with ambient humidity. The cured coating provides excellent ease of removal from most permanent markers and spray paints.

Properties

- Graffiti removal with cold water
- Resistant to inclement weather
- Water resistant
- Permeable to water vapor
- Solvent dilutable and environmentally friendly
- Improves surface color

Technical data

Consumption	0.2 kg / m ²
Minimum application temperature	+5°C
Drying	3-5 h. (20°C, 60% H.R)
UV resistance	High
Pressure water resistance	Up to 100 bar

Application

The surfaces to be protected must be clean and dry. It can be applied with a brush, roller and airless.

Graffiti removal is done by simply applying cold water.

Storage

ANTIGRAFFITIK is presented in airtight and approved containers in accordance with EU guidelines for the packaging and storage of chemical products. Avoid frost and temperatures above 35° C. The product can be stored for one year in original, closed containers and covered places.

Precautions

In case of contact with eyes, wash them with plenty of clean water and consult a doctor. Hands and skin should be washed with soap and hot water. Avoid release to the environment.